



Certificate of Calibration and Compliance

Manufacturer	:	Viavi Solutions
Model Number	:	Certifier40G
Description	:	NGC-4500-FA
Country of Manufacture	:	MALAYSIA
Serial Number	:	jw20302223
Calibration Report Number	:	20302223-20200309
Calibration Date	:	March 9, 2020
Ambient Temperature	:	(23 ± 3) °C
Relative Humidity	:	30% to 70%

Viavi Solutions certifies that at the time of shipment the above listed instrument as identified by its serial number meets or exceeds all published specifications. It has been calibrated using standards with accuracies that are traceable to the National Institute of Standards and Technology (NIST) or other national laboratories. Accuracies have been derived from accepted values of physical constants, or have been derived by ratio type of self-calibration technique.

Calibration Interval:

The instrument has a calibration cycle of 12 months. Calibration does not deteriorate during storage prior to putting the instrument in active use. Calibration cycle of the instrument can be considered to start on the date the instrument was purchased by end user. First re-calibration will become due 12 months from that date.

Certificate Date
March 9, 2020

Viavi Solutions
Viavisolutions.com



Avda. Manoteras, 26 - 5°C
28050 Madrid
Tel.: 91 383 98 01
C.I.F.: B-78431483



Certificate of Calibration and Compliance

Manufacturer : Viavi Solutions
Model Number : Certifier40G
Description : NGC-4500-FA
Country of Manufacture : MALAYSIA
Serial Number : jw20302224
Calibration Report Number : 20302224-20200309
Calibration Date : March 9, 2020
Ambient Temperature : (23 ± 3) °C
Relative Humidity : 30% to 70%

Viavi Solutions certifies that at the time of shipment the above listed instrument as identified by its serial number meets or exceeds all published specifications. It has been calibrated using standards with accuracies that are traceable to the National Institute of Standards and Technology (NIST) or other national laboratories. Accuracies have been derived from accepted values of physical constants, or have been derived by ratio type of self-calibration technique.

Calibration Interval:

The instrument has a calibration cycle of 12 months. Calibration does not deteriorate during storage prior to putting the instrument in active use. Calibration cycle of the instrument can be considered to start on the date the instrument was purchased by end user. First re-calibration will become due 12 months from that date.

Certificate Date
March 9, 2020

Viavi Solutions
Viavisolutions.com



Avda. Manoteras, 26 - 5°C
28050 Madrid
Tel.: 91 383 98 01
C.I.F.: B-78431483